

ST-5032

DVB-S2/S, DVB-T/T2,DVB-C Signal Finder

This is a fully DVB-S2/S,DVB-T/T2,DVB-C compliant handheld signal finder .It has many useful features, etc compact size,lightweight; intuitive user's interface;long battery operational;multiple parametersIn particular, it has the measurement function of voltage for the main line.

KEY FEATURES



TECHNICAL SPECIFICATIONS

TRANSMISSION STANDARDS	
DVB-S2/S, DVB-T/T2,DVB-C	
SATELLITE INPUT/DEMODULATION	
Connector Type	F Type
Input Frequency	950 to 2150 MHz
Signal Input Level	0~-80 dBm
Band Switch Control	22KHz
LNB Supply	13V/18V, IMax 350mA
Demodulation Type	QPSK,8PSK,16APSK
Symbol Rate	2<Rs<45Mband(SCPC/MCPC)
DVB-T/T2 INPUT/DEMODULATION	
Connector Type	F Type
Input Frequency	48 to 862 MHz
Signal Input Level	0 ~ -80dbm
Demodulation Type	16QAM,64QAM,256QAM(DVBT2)
DVB-C INPUT/DEMODULATION	
Connector Type	F Type
Input Frequency	48 to 862 MHz
Signal Input Level	0 ~ -67dBm
Demodulation Type	64QAM,256QAM
LCD FEATURES	
LCD Type	TFT Transmissive
Number of Dots	320 (RGB) x240
LCD screen	2.4"
DATA SERVICE PORT	
Connector	USB
Data Protocol	USB2.0 interface
F i l e M a n a g e m e n t System	NTFS,FAT32
File Format	wma,mp3,avi,jpg,jpeg,bmp etc
POWER SUPPLY	
Li - ion Battery	7.4V/2600mAh
Adapter	OUTPUT :DC12V/1A, INTUPT :100~240VAC 50/60Hz
Power Consumption	Max. 10W
PHYSICAL CHARACERSTICS	
Size (W x D x H)	17x 8x 4 (cm3)
Net Weight	about 0.7kg